



Screenshots for ZEN Imaging Software & CoolLED Bridge Software

CoolLED Bridge



CoolLED Bridge Setup Wizard





👹 CoolLed Bridge Setup		×
Product Activation Please enter your activation code		₩¥
Activaton code:		
	Back Next	Cancel

Activation Code Input

pE-4000 config		
Reflector		Channels
	r	none 🔻
	r	none 🔻
50 Cy 5	r	none 🔻
	r	none 🔻
	r	none
	Save	560
	7	740 💾
	7	770

pE-4000 Config Tool for the CoolLED Bridge: This allows pE-4000 channel selection





🕾 CoolLed Bridge Config Tool
Enable Debug Log
Enable Error Log
Reset Revolver Settings
Close

CoolLED Bridge Config Tool: Debugging, Error Logging and Reset

File Action View Help Image: Services (Local) Image: Services (Local) Image: Services (Local) CoolLed Service Name Description Status Startup Type Log On As Stop the service Background Intelli Transfers fil Started Automatic (D Local Syste. Base Filtering Engi The Base Fil Started Automatic Local Syste. Image: BitLocker Drive En BDESVC hos Manual Local Syste.	Services					\Leftrightarrow	
Image: Services (Local) Image: Services (Local) CoolLed Service Name Description Status Startup Type Log On As Stop the service Stop the service Background Intelli Transfers fil Started Automatic (D Local Syste. Base Filtering Engi The Base Fil Started Automatic Local Syste. BitLocker Drive En BDESVC hos Manual Local Syste.	File Action View	/ Help					
Services (Local) Services (Local) CoolLed Service Name Description Status Startup Type Log On As Stop the service Stop the service Background Intelli Transfers fil Started Automatic (D Local Syste. Base Filtering Engi The Base Fil Started Automatic Local Syste. BitLocker Drive En BDESVC hos Manual Local Syste.		Q 📑 🛛 📰 🕨 🔲 II 🕪					
CoolLed Service Name Description Status Startup Type Log On As Stop the service Background Intelli Transfers fil Started Automatic (D Local Syste. Restart the service Base Filtering Engli The Base Fil Started Automatic Local Syste. BitLocker Drive En BDESVC hos Manual Local Syste.	Services (Local)	O Services (Local)					
Stop the service Stop the service Stated Automatic (D Local Syste. Restart the service Stated Stated Automatic Local Syste. Stop the service Stated Stated Automatic Local Syste. Restart the service Stated Stated Automatic Local Syste. Stated Stated Automatic Local Syste. Stated Stated Automatic Local Syste. Stated Stated Manual Local Syste.		CoolLed Service	Name	Description	Status	Startup Type	Log On As 🔺
Description: Connects CoolLed to MTB server (2.3.0.13) Block Level Backu The WBENG Manual Local Syste. Bluetooth Support The Bluetoo Manual Local Syste. BranchCache This service Manual Local Syste. Certificate Propag Copies user Started Manual Local Syste. COM+ Event Syst Supports Sy Started Automatic Local Syste. COM+ System Ap Manual Local Syste. COM+ System Ap Manual Local Syste. Computer Browser Maintains a Started Manual Local Syste. CoolLed Service Connects C Started Automatic Local Syste. CoolLed Service Connects C Started Automatic Local Syste.		Stop the service Restart the service Description: Connects CoolLed to MTB server (2.3.0.13)	 Background Intelli Base Filtering Engi BitLocker Drive En Block Level Backu Bluetooth Support BranchCache Certificate Propag CNG Key Isolation COM+ Event Syst COM+ System Ap Computer Browser CoolLed Service Credential Manager 	Transfers fil The Base Fil BDESVC hos The WBENG The Bluetoo The Bluetoo The Service Copies user The CNG ke Supports Sy Manages th Maintains a Connects C Provides se	Started Started Started Started Started Started	Automatic (D Automatic Manual Manual Manual Manual Manual Automatic Manual Automatic Manual Automatic Manual	Local Syste. Local Servic Local Syste. Local Syste. Local Servic Network S Local Syste. Local Syste. Local Syste. Local Syste. Local Syste. Local Syste. Local Syste.
Cryptographic Ser Provides Ser Manual Local Syste. Cryptographic Ser Provides fo Started Automatic Network S CZCanSrv Started Manual Local Syste. DCOM Server Pro The DCOM Started Automatic Local Syste. DCOM Server Pro The DCOM Started Automatic Local Syste. Desktop Window Provides De Started Automatic Local Syste. DHCP Client Registers an Started Automatic Local Syste. Diagnostic Policy The Diagno Started Automatic Local Servic Diagnostic Service The Diagno Started Manual Local Servic Diagnostic Service The Diagno Started Manual Local Servic Extended Standard		Extended Standard	Cryptographic Ser CZCanSrv DCOM Server Pro Desktop Window DHCP Client Diagnostic Policy Diagnostic Service	Provides Se Provides fo The DCOM Provides De Registers an The Diagno The Diagno	Started Started Started Started Started Started Started	Automatic Manual Automatic Automatic Automatic Automatic Manual	Network S Local Syste. Local Syste. Local Syste. Local Servic Local Servic Local Servic

Windows Services: 'CoolLED Service' should be 'started'



<u>ZEN</u>

MTB2011 Configuration 2.3.0.13		
File Options ?		
Image: Configuration 2.30.13 File Options ? Auto Configuration New Configuration Configuration New Configuration Options ? Configuration New Configuration No Defiguration No Definite Focus No Definite Focus No Perco Focus Holder for Obtovar Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Sidepot Turet Path Deflection to the Tube X Motorized Path Path Deflection tot	Filter: Name / KL bt. Motorzed Path Defecting Nimor KL bt. Marual Path Deflecting Mimor KL bt. Marual Path Deflectin	
BC34: Beam Combiner 5 Pos4: LED-Module 625n No Collibri Shutter Empty Lamp Port Empty Lamp Port RL No Beam Path Switching No Metorized Shutter RL No Fieldstop No ApoTome RL No Apoture Stop/FL Atte Transmitted Light Manual Tubs To Lamer Module Zaise Inclustor		
Offine	OK Cancel Ready	Apply

MTB Configuration: Hardware needs to be simulated for a CoolLED Product



👻 🖪 Ligh	t Path			✓ Show All		
	Interactive		Settings	Editor		
Bright Field	Closed	ov ?				
	Stage ,	0,00 µm Focus				
10x						4
49 DAPI	Closed	Colibri/Colib	C. 114 - D			n Show All I
Ţ		Colibri/	Colibri.2	- 470		
100% VIS		365	1 365	470		19.8 % 🛟
17		Continu	ous	Gated	Deact	ivate all LEDs
ΨŲ.						
Microscope	TL					

ZEN GUI: The CoolLED system mimics the Colibri/Colibri.2





ZEN GUI: Breakdown of Light path



